

Product No: CA522E

ABB CONTACT AUX 2NO/2NC T-S -00 CA522E



General Information

Brand	ABB
Product Type	Accessory
Suitable For	AF45, AF50, AF63, AF75, AF95B, GAF75, A9, A16, A26, A45, A50, A63, A75, A95, A110, AL9, AL16, AL26, AE45, AE50, AE63, AE75, TAL9, TAL16, TAL26, TAE45, TAE50, TAE75, GA75, GAE75, UA50, UA63, UA75, UA95, UA110

Technical Attributes

Clamp Type	Screw Terminals
Maximum Electrical Switching Frequency	1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mechanical Durability	10 million 3 million
No. of Auxiliary Contacts	2 NO + 2 NC
Rated Frequency (Hz)	50 / 60
Rated Insulation Voltage	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (A)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Voltage AC (V)	Auxiliary Circuit 690 V
Rated Short-time Withstand Current Low Voltage - I _{cw} (A)	for 0.1 s 140 A for 1 s 100 A

Dimensions

Dimensions (mm)	47 * 44 * 39 [H*W*D]
-----------------	----------------------

Protection & Standards

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
----------------------	---
