

Product No: CP1-30G-10

ABB NON-ILLUMINATED PUSHBUTTON CHROME METAL GREEN
INO INC CP1-30G-10

FEATURES

- Compact, space-saving design
- Durable, high dust and water resistance
- Ideal for quick activation
- Non-illuminated green indication



General Information	
Brand	ABB
Enclosure Type (NEMA)	Type1, Type12, Type13, Type3R, Type4, Type4X
Product Type	Pushbutton
Technical Attributes	
Connecting Capacity	Flexible with Ferrule 1/2 x 0.5 – 1.5mm ² Flexible with Insulated Ferrule 1/2 x 0.5 – 1.5mm ² Flexible 1/2 x 0.5 – 1.5mm ² Solid 1/2 x 0.5 – 1.5mm ²
Connection Type	Screw Clamp
Function	Momentary
No. of Normally-open Contacts	1
Power Loss (W)	Maximum 2.5W
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	300
Rated Operational Current AC-15 240V (A)	1
Rated Operational Current DC-13 125V (A)	0.2
Rated Operational Current DC-13 24V (A)	0.3
Rated Operational Voltage (V)	300
Terminal Type	Screw
Tightening Torque (Nm)	0.8
Wire Stripping Length (mm)	6



Physical Attributes

Actuator Type	Flush
Ambient Temperature Range (°C)	-25 to 70
Colour	Green
Material	Bezel: Chrome Metal
Storage Temperature Range (°C)	-40 to 85

Dimensions

Dimensions (mm)	30W x 30H x 55D
Weight (kg)	0.033

Protection & Standards

Degree of Protection	Front: IP66, IP67, IP69K; Terminals: IP20
Pollution Degree	3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------