

Catalogue No: **90.26**

## BASE FOR 6012 RELAY BOX CLAMP W/METAL CLIP

Timers and Control Relays > General Purpose Relays > Electromechanical Relays > Finder Electromechanical Relays > Power Relays > 60 Series Square Base Relays

**NHP**



Representative Photo Only  
(actual product may vary based on configuration selections)

### Base For 6012 Relay Box Clamp w/Metal Clip

- Complete range from PCB to power relays to cover all of your switching requirements
- International certifications and approvals including CE, CSA, EAC, PCT, RINA, VDE and RoHS, providing quality assurance of a market leading product
- Compact construction allowing for most efficient use of your space


#### SPECIFICATIONS

Product Series	60
Component Type	Timers and Control relays
Relay Type	Relay Base
Electrical Service Life at Un, In	200000 cycles
Total Making Time	11 ms
Total Breaking Time	4 ms
Insulation Voltage, between Coil & Contacts	4000 V
Dielectric Strength, between open Contacts	1000 V AC
Mounting	Plug-in
Operating Temperature, Min	-40 °C min
Operating Temperature, Max	70 °C max
Height	51 mm
Width	33 mm
Depth	23 mm
Shock Acceleration (Max.)	20 g
Shock Duration (Max.)	4 ms
Vibration Acceleration (Max.)	22 m/s <sup>2</sup>
Vibration Frequency, Operational (Max.)	55 Hz
Certifications	CE CCC CSA EAC GOST-R IMQ VDE C-UR-US

Shipping Approvals

Lloyd's Register of Shipping  
RINA (Registro Italiano Navale)

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-




Dimension Diagram

Catalogue No: **90.26**

**BASE FOR 6012 RELAY BOX CLAMP W/METAL CLIP**

Timers and Control Relays > General Purpose Relays > Electromechanical Relays > Finder Electromechanical Relays > Power Relays > 60 Series Square Base Relays



**90.26**

Connection / Wiring Diagram