

# Catalogue No: **D7-A6PR5**

## PROTECTIVE YELLOW GUARD FOR EMERGENCY STOP OPERATORS 85mm

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Accessories > Protective Guards



### Pushbutton Guard, Yellow For Emergency Stop



Representative Photo Only  
(actual product may vary based on configuration selections)

- D7 pilot devices offer maximum flexibility and a wide choice for all 22.5mm operator applications with all type (e-stops, selector switches, pushbuttons, pilot lights and more), colour and contact configurations.
- Aesthetically appealing and modularly designed to make assembly and interchangeability easy.
- Operators exhibit low profile and stylish appearance while maintaining the rugged performance necessary for demanding environments
- D7P is a plastic operator with a captive black plastic front bezel. Constructed of high-grade thermoplastics, the D7P is suitable for almost all environments and strong chemical resistance.
- D7M has a die-cast zinc housing and mounting ring for rugged durability. Finished with corrosion resistant chrome plating, the D7M also features a captive shiny metal bezel for a polished appearance.

#### SPECIFICATIONS

|  |  |
|--|--|
| Product Series                             | D7A  |
| Component Type Pushbutton and Pilot Lights | Accessories - General  |
| Compatible Product Series'                 | D7 22.5mm Control & Indication   |
| Details, compatible product series         | For Emergency Stop Operators   |
| Colour                                     | Yellow   |
| Material                                   | Plastic  |
| Diameter                                   | 85 mm  |
| RoHS Approved                              | Yes  |
| CE Marked                                  | Yes  |
| Relative humidity, min                     | 50 %RH   |
| Relative Humidity, Max                     | 95 %RH   |
| IP Rating                                  | IP66<br>IP65   |
| Shock Acceleration (Max.)                  | 100 g  |
| Shock Duration (Max.)                      | 11 ms  |
| Vibration Acceleration (Max.)              | 10 m/s <sup>2</sup>  |
| Vibration Displacement (Peak to Peak Max.) | 1.52 mm  |
| Vibration Frequency, Operational (Max.)    | 2000 Hz  |
| Vibration Duration (Max.)                  | 180 min  |
| Standards Compliance                       | NEMA ICS-5<br>UL 508<br>EN 60947-1<br>EN 60947-5-1<br>EN 60947-5-5<br>EN 418 |
| Certifications                             | UL<br>UR<br>CSA<br>CCC<br>CE   |

# Catalogue No: **D7-A6PR5**

## PROTECTIVE YELLOW GUARD FOR EMERGENCY STOP OPERATORS 85mm

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Accessories > Protective Guards



Shipping Approvals

RINA (Registro Italiano Navale)  
ABS (American Bureau of Shipping)  
Lloyd's Register of Shipping

### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: [D7A6PR5\\_Manufacturer Datasheet](#)

Manufacturer Catalogue  
& Product Selection: -