

Catalogue No: **D7-AP0**

LENS CAP FOR PILOT AMB

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Pilot Lights > Lens Caps for Pilot Lights (Spares / Replacements)



Lens cap for pilot Amber

- D7 pilot devices offer maximum flexibility and a wide choice for all 22.5mm operator applications with all type (e-stops, selector switches, pushbuttons, pilot lights and more), colour and contact configurations.
- Aesthetically appealing and modularly designed to make assembly and interchangeability easy.
- Operators exhibit low profile and stylish appearance while maintaining the rugged performance necessary for demanding environments
- D7P is a plastic operator with a captive black plastic front bezel. Constructed of high-grade thermoplastics, the D7P is suitable for almost all environments and strong chemical resistance.
- D7M has a die-cast zinc housing and mounting ring for rugged durability. Finished with corrosion resistant chrome plating, the D7M also features a captive shiny metal bezel for a polished appearance.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--|---|
| Component Type Pushbutton and Pilot Lights | Pilot Light |
| Diameter, lens | 29.6 mm |
| Colour, Lens | Amber colour |
| Material, Lens | POM / Acetal / Polyacetal / Polyformaldehyde (Polyoxymethylene) |
| Coupling Plate Included | No Y / N |
| Lamp Module Included | No |
| Mounting | 22.5mm Mounting |
| Compatible Product Series | D7 22.5mm Control & Indication compatible |
| Dielectric Strength | 2.5kV for 1 minute |
| RoHS Approved | Yes |
| CE Marked | Yes |
| Operating Temperature, Max | 70 °C max |
| Operating Temperature, Min | -25 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -25 °C min |
| Relative humidity, min | 50 %RH |
| Relative Humidity, Max | 95 %RH |
| IP Rating | IP66 IP65 |
| Shock Acceleration (Max.) | 100 g |
| Shock Duration (Max.) | 11 ms |
| Vibration Acceleration (Max.) | 10 m/s ² |
| Vibration Displacement (Peak to Peak Max.) | 1.52 mm |
| Vibration Frequency, Operational (Max.) | 2000 Hz |
| Vibration Duration (Max.) | 180 min |

Catalogue No: **D7-AP0**

LENS CAP FOR PILOT AMB

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7
Pushbuttons and Pilot Lights > D7 Pilot Lights > Lens Caps for Pilot Lights (Spares / Replacements)



Standards Compliance

NEMA ICS-5
UL 508
EN 60947-1
EN 60947-5-1
EN 60947-5-5
EN 418

Certifications

UL
UR
CSA
CCC
CE

Shipping Approvals

RINA (Registro Italiano Navale)
ABS (American Bureau of Shipping)
Lloyd's Register of Shipping

REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

-

Installation Guide:

-

User Manual:

-

Manufacturer Datasheet:

[Series D7_Manufacturer Datasheet](#)

Manufacturer Catalogue
& Product Selection:

-