

Catalogue No: **E125NJ4100**

TB2 MCCB 25kA 4P 100A THERMAL MAGNETIC

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 125 AF > Thermal Magnetic 125 AF 25kA



T2 MCCB 25kA 4P 100A

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	TemBreak 2 MCCB
Component Type MCCB	MCCB AC
Poles	4P
Frame Size	125 AF size
Rated Frequency	50 / 60 Hz
Trip Unit Protection Type	Adjustable Thermal Adjustable Magnetic
Ue, Rated Operational Voltage, AC, max	525 V AC
Uimp, Impulse Withstand Voltage	8 kV
Ui, Rated Insulation Voltage	800 V (rms)
In, Rated Current at 45°C	100 A @45°C
Ics, Rated Service Short-Circuit Breaking Capacity, AC (IEC 60947)	76 % Icu
Ics, Rated Service Short-Circuit Breaking Capacity, DC	76 % Icu
Ics, Rated Service Short-Circuit Breaking Capacity, 240V AC	35 kA
Ics, Rated Service Short-Circuit Breaking Capacity, 525V AC	6 kA
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 250V DC	25 kA @250VDC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 240V AC	35 kA @240VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 400V AC	25 kA @400VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 400/415V AC	25 kA @400/415VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 415V AC	25 kA @415VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 440V AC	15 kA @440VAC
Icu, Rated Ultimate Short-Circuit Breaking Capacity, 525V AC	8 kA @525VAC
Number of Poles	4
Height	155 mm

Catalogue No: **E125NJ4100**

TB2 MCCB 25kA 4P 100A THERMAL MAGNETIC

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 125 AF > Thermal Magnetic 125 AF 25kA



Width	120 mm
Depth	68 mm
Weight	1.4 kg
Standard Installation Method	Front Connection
Reverse Connection Of Supply Possible	Yes
Electrical Service Life at Un, In	30000 cycles
Mechanical Service Life	30000 cycles
Standards Compliance	IEC 60947-2 EN 60947-2 JIS C 8201-2-1 Ann.1 NEMA AB1 AS/NZS 60947-2
Thermal Trip Type	Adjustable type
I _r , Thermal Trip Current, Min	63 A
I _r , Thermal Trip Current, Max	100 A
Magnetic Trip Type	Adjustable type
I _m , Magnetic Trip Current, Min	600 A
I _m , Magnetic Trip Current, Max	1200 A
Certifications	ASTA
Shipping Approvals	Contact NHP

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-