

Catalogue No: **KL1049646**

BUZZER BASE MOUNT 80dB 450Hz IP34 6-14V DC

Signalling Devices > Sound Indication > Buzzers, Hooters and Bells > Moflash Buzzers, Hooters and Bells > Buzzer > KKTB Compact Buzzers



Representative Photo Only
(actual product may vary based on configuration selections)

Base or surface mount 450 Hz buzzer, 6-14V DC IP34 80 dB

- Wide range including piezo-electric buzzers, motor driven hooters and mechanical bells to suit all requirements
- Piezo buzzers can be visually discreet and produce constant frequency output from 80 to 110dB dependent on model which is perfectly suited to simple signalling applications
- Motor driven hooters provide moderate dB output with an extremely recognizable sound
- Mechanical bells provide the traditional school bell sound in a sturdy construction that will stand the test of time

SPECIFICATIONS

IP Rating	IP34
Ue, Rated Operational Voltage, DC, min	6 V DC
Ue, Rated Operational Voltage, DC, max	14 V DC
In, Rated Current	0.03 A
Sound Mode	Continuous mode
Frequency, Sound Output	450 Hz
Sound Level @1m	80 dB @1m

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-