



## LED BEACONS

### MOLED 125

The MOLED 125 incorporates 48 LEDs in one enclosure and has two modes of operation, static and flashing (switch selectable on PCB). Suitable for use in harsh conditions; Beacon includes multiple LED's, base and dome.



#### TECHNICAL SPECIFICATION

<b>IP RATING:</b>	IP 65
<b>CASING:</b>	Polycarbonate dome / ABS base
<b>OPERATING TEMP:</b>	-20 °C to + 45 °C
<b>WEIGHT:</b>	270 grams

VOLTAGE	LIGHT SOURCE	CURRENT	ORDER CODES
24 V DC	48 LED Array	200 mA	<b>MOLED125-02_1)</b>
110 V AC	48 LED Array	6 mA	<b>MOLED125-03_1)</b>
240 V AC	48 LED Array	3 mA	<b>MOLED125-04_1)</b>

Steel guard - plastic coated	<b>MO50003</b>
Spare Amber dome	<b>MO50019</b>
Spare Red dome	<b>MO50018</b>
Wall mount bracket - right angle	<b>MO50001</b>
Anti vibration mount	<b>MO50080</b>

#### NOTES:

1) Add letter R or A to end of Cat. No. for colour of dome.

Not recommended for areas of high vibration.

\* Internal link on PCB for static (s) or flash (f).

\* Hard wired with 200 mm cables

