



XENON BEACONS

MOX 500/501

The MOX 500/501 beacon provides a 24 joule flash at 60 flashes per minute and 18 joule "double flash" at 90 flashes per minute. This beacon has a 150 mm \varnothing base size, like the 400/401 range. Beacon includes dome, base and lamp.



TECHNICAL SPECIFICATION

IP RATING	IP 65
CASING	Polycarbonate dome / ABS base
OPERATING TEMP:	-25 °C to + 66 °C
WEIGHT:	1.25 Kg

VOLTAGE	LIGHT SOURCE	CURRENT	ORDER CODES
12 / 24 V DC	Xenon 24/18 joule	2.3 A	MOX501-18_1) ²⁾
110 V AC	Xenon 24/18 joule	650 mA	MOX500-21_1)
240 V AC	Xenon 24/18 joule	400 mA	MOX500-22_1)

Steel guard - plastic coated	MO50010
Spare Amber dome	MO50064
Spare Red dome	MO50065
Spare Blue dome	MO50066
Spare Green dome	MO50067
Wall mount bracket - right angle	MO50004
Single point mount bracket	MO50006

NOTES:

¹⁾ Add letter R, A, G or B at end of order code to denote dome colour.

²⁾ The MOX501-18_ is pre-set to 24 V DC.

XS0104 (bi lateral current limiter) to be used where power direct from batteries or battery backed power supply.