Catalogue No: **NUSSCNPAK**

SELECTOR SWITCH 30.5mm 2 POS S/LEVER STAY 2X45deg 1NO 1NC

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Austrol N100 Pushbuttons > Complete N100 Panel Mounted 30.5mm Standard Units > Complete Selector Switches with Contact Block





Representative Photo Only (actual product may vary based on configuration selections)

Selector Switch 30.5mm 2 Pos S/Lever Stay 2X45Deg 1NO 1NC

- Engineered and manufactured in Australia, the N100 30.5mm range of heavy duty control elements are made to meet the harshest operating environments.
- Customisable and modular the N100 range includes pushbuttons, pilot lights, selector switches, estops and more, with a wide range of accessories to ensure a complete selection for your installation.
- Self-wiping contacts with a unique rolling action ensures every operation removes any dust or nonconductive film and prolongs the life of your components.

SPECIFICATIONS	
Product Series	N100
Component Type Pushbutton and Pilot Lights	Selector Switch
Operator Type	Selector Switch, Lever, 2-Position type
Key	No Y/N
Operator Position, Right	45° Right
Operator Action, Right	Latched / Maintained
Material, Operator	Chrome-Plated Zinc Alloy material
Mounting	Panel Mount
Contact Block Included	Yes
Contact Configuration	1 NO + 1 NC
In, Rated Current	10 A
le, Rated Operational Current, AC-12, 110V	10 A@110V
le, Rated Operational Current, AC-12, 240V	10 A@240V
le, Rated Operational Current, AC-12, 415V	5 A@415V
le, Rated Operational Current, AC-15, 110-120V	6 A@110-120V
le, Rated Operational Current, AC-15, 240V	3 A@240V
le, Rated Operational Current, AC-15, 415V	1.5 A@415V
le, Rated Operational Current, DC-12, 32V	10 A@32V
le, Rated Operational Current, DC-12, 110V	5 A@110V
Terminal Type	Screw Terminal(s)
RoHS Approved	Yes
Operating Temperature, Max	80 °C max
Operating Temperature, Min	-30 °C min
Storage Temperature, Max	80 °C max
Storage Temperature, Min	-30 °C min
IP Rating	IP66



Catalogue No: **NUSSCNPAK**

SELECTOR SWITCH 30.5mm 2 POS S/LEVER STAY 2X45deg 1NO 1NC



Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Austrol N100
Pushbuttons > Complete N100 Panel Mounted 30.5mm Standard Units > Complete Selector Switches with Contact
Block

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

