



- Quality design at an economical price
- Standard electronic motor protection with improved phase loss protection, class 10 trip overload curve
- RZ7 Electronic timer with adjustable changeover time (1.5 to 30 seconds)

Open type star delta starters mounted on a metal base plate

kW @ 400/415 V AC	Main & Delta contactors	Star contactors	Standard overload ¹⁾	Overload setting range ²⁾ (A)	Cat No.
3...7.5	CA 7-9	CA 7-9	CEP 7-M32-12-10	3.7-12	O-SDS 7-7.5
11	CA 7-12	CA 7-9	CEP 7-M32-32-10	12-32	O-SDS 7-11
15	CA 7-16	CA 7-9	CEP 7-M32-32-10	12-32	O-SDS 7-15
18.5	CA 7-23	CA 7-12	CEP 7-M32-32-10	12-32	O-SDS 7-18.5
22	CA 7-23	CA 7-16	CEP 7-M32-32-10	12-32	O-SDS 7-22
30...37	CA 7-37	CA 7-23	CEP 7-M45-45-10	14-45	O-SDS 7-37
37...45	CA 7-60	CA 7-30	CEP 7-M85-85-10	26-85	O-SDS 7-45
55	CA 7-60	CA 7-37	CEP 7-M85-85-10	26-85	O-SDS 7-55
75	CA 7-85	CA 7-43	CEP 7-M85-85-10	26-85	O-SDS 7-75

Notes: Add control voltage to Cat No. when ordering. (240 volt or 415 volt AC).

¹⁾ If required a class 20 overload can be provided.

²⁾ For motor full load amps below 6.4 A a lower scale setting is available.

240/415 V rated coils are suitable for use on 230/400 V in accordance with AS 60068 : 2000