Catalogue No: PCS-016-480V

PCS SOFT STARTER 480V 16A ND3W 100-240V AC CONTROL

Motor Control and Drives > Soft Starters, Low Voltage > Industrial Soft Starters > Sprecher + Schuh Soft Starters > PCS Soft Starters > Panel Mount - IP2X 200 to 480V AC Three-Phase with 100 to 240V AC Control Power





(actual product may vary based on configuration selections)

SPECIFICATIONS

Soft starter 7.5KW with motor protection, supply voltage 480V AC, control voltage 100...240V AC

- Integral bypass minimises heat generation allowing for reduced enclosure size and reduced total cost
- Ultra-compact size means reduced panel space and allows for higher-density installations
- Easy and secure setup allows for process optimisation and setup efficiency
- LED indicator gives instant status information and assists during troubleshooting

IP Rating	IP00
Component Type Motor Control and Drives	LV Soft Starter
Rated Current, Light Duty, 3 Wire	16 A, 3 wire
Rated Current, Normal (Medium) Duty, 3 Wire	16 A, 3 wire
Medium Duty Approx. kW (400/415 V AC, 3 wire)	7.5
Inbuilt Motor Protection	Yes, standard
Bypass Contacts	Yes, internal
Control Voltage	110 - 240 V AC
Control Voltage, AC, Min	100 V AC min
Control Voltage, AC, Max	240 V AC max
Height	140 mm
Width	45 mm
Depth	100 mm
REFERENCES	
IECEx Certificate -	
Supplier Declaration of Conformity:	
Installation Guide: -	
User Manual: -	
Manufacturer Datasheet: -	
Manufacturer Catalogue & Product Selection:	

