PRODUCT DATASHEET
DULUX S 9 W/0 G23

OSRAM DULUX S | Short CFLni, with 2-pin base for CCG operation

AREAS OF APPLICATION

– Ideal for cost-effective creative illumination and decoration
– Offices, public buildings
– Shops
– Supermarkets and department stores
– Hotels, restaurants

PRODUCT BENEFITS

– Extremly economical
– Good quality of light
– Extremely low profile
– Long service life
– Improved maintenance

PRODUCT FEATURES

– Average life: 10,000 h
– Color rendering index R_a for lamps with white light: 80...89
– Also available in red, green and blue
– Short and compact pin-base lamps with single-turn tubes
– Single-ended two-pin plug-in G23 base

TECHNICAL DATA

Electrical data

Nominal wattage	9.00 W
Rated wattage	9.00 W

Photometrical data

Luminous flux at 25 °C	570 lm
Color rendering index Ra	80...89

Dimensions & weight

Diameter	12.0 mm
Overall length	167.0 mm
Length	167.0 mm
Length acc. to IEC standard	145 mm
Length with base excl. base pins/connection	144.00 mm
Outer bulb	T12X3

Lifespan

Nominal lamp life time	8000 h
Rated lamp life time	8000 h
Lifespan	10000 h [1]

[1] With CCG/LLCG

Additional product data

Base (standard designation)	G23
Mercury content	3.0 mg

EQUIPMENT / ACCESSORIES

– Suitable for operation on conventional control gear

Others graphics

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321664310	DULUX S 9 W/0 G23	Shipping carton box 10	190 mm x 53 mm x 184 mm	1.85 dm³	492.00 g
4050300923949	DULUX S 9 W/0 G23	Shipping carton box 100	510 mm x 200 mm x 204 mm	20.81 dm³	5465.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.