

# Product Characteristics

**Part Number: CBL10BWEW500**

CABLE BUILDING WIRE EARTH WIRE 10MM 7/135 1C 500M G/Y

## Description:



Single core PVC V90 insulated building wire. This cable is commonly used for residential and light to medium commercial installations. Used for switchboard and control panel wiring. Suitable for glanding. Available in all commonly required colours. Uninsulated or Green/Yellow coloured building wire is used where an earth wire is run separately.

Attribute Name	Attribute Value
Nominal voltage U	0.6 kV
Material outer sheath	PVC
Nominal voltage U0	1 kV
Conductor category	Class 2 = Stranded
Nominal cross section conductor	10 mm <sup>2</sup>
Permitted cable outer temperature, fixed	90 °C
Outer diameter approx.	6 mm
Colour outer sheath	Green/Yellow
Insulation thickness	1 mm

Classifications	
ETIM	EC000057
UNSPSC	26121629

Create Date:

## Disclaimer

*For use on datasheets that are created by Rexel*

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.