Product Characteristics

GENERIC CABLE 0.752CODFXBK

CABLE FLEX ORDINARY DUTY 0.75MM 24/020 2C 100M BLACK SHEATH

Our Number:	CBL0.752CODFXBK	Supplier Number:	0.752CODFXBK
EAN Number:			

Product Description

Flexible cable comprises of multiple individually insulated cables contained in a round outer sheath. Used where flexibility is required such as power supply leads for moveable equipment or controls. Typically is als used in domestic and industrial extension leads. Suitable for glanding.



Technical Specifications

Attribute Name	Attribute Value	
Nominal cross section conductor	0.75 mm ²	
Conductor material	Copper	
Core identification	Colour	
Material outer sheath	PVC	
Colour outer sheath	Black	

Classifications	
ETIM	RC900003
UNSPSC	

http://rappdcpimusrprd.rapac.com.au:1512/pim/webaccess/preview?template=Product+Characteristic+Sheet&entities=752140%401&entityType=Article[20/11/2024 8:23:34 AM]

Disclaimer

For use on datasheets that are created by Rexel

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.