

# Product Characteristics

**Part Number: CBL1.54CEOCOR**

CABLE ORANGE CIRCULAR 1.5MM 7/050 4C+E 100M 450/750V



## Description:

Orange circular cable is suitable for mains, sub mains and sub circuits unenclosed, enclosed in conduit buried direct or underground ducts for buildings and industrial plants where not subject to mechanical damage. Even though this cable is suitable for burial, it is not considered waterproof so is suitable for use where the ground may become wet or saturated for relatively short periods. Typically used in industrial and commercial installations. Suitable for glanding.

| Attribute Name                           | Attribute Value     |
|--|---------------------|
| Operating voltage                        | 750 V               |
| Core identification                      | Colour              |
| Nominal cross section conductor          | 1.5 mm <sup>2</sup> |
| Stranding                                | 7/0.50              |
| Conductor material                       | Copper              |
| Colour outer sheath                      | Orange              |
| Core insulation                          | PVC                 |
| Permitted cable outer temperature, fixed | 90 °C               |
| With earthing                            | Yes                 |
| Conductor category                       | Class 2 = Stranded  |
| Number of cores                          | 5                   |
| Material outer sheath                    | PVC                 |
| Outer diameter approx.                   | 12.2 mm             |
| Earthing cable cross section             | 1.5 mm <sup>2</sup> |

| Classifications |          |
|-----------------|----------|
| ETIM            | EC000057 |
| UNSPSC          | 26121629 |

Create Date:

## Disclaimer

*For use on datasheets that are created by Rexel*

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.