

# Product Characteristics

**Part Number: CBL1.54CODFXOR**

CABLE FLEX ORDINARY DUTY 1.5MM 30/025 4C 100M ORANGE SHEATH

## Description:



Flexible cable comprises of multiple individually insulated cables contained in a round outer sheath. Used where flexibility is required such as power supply leads for moveable equipment or controls. Typically is also used in domestic and industrial extension leads. Suitable for glanding.

Attribute Name	Attribute Value
Permitted cable outer temperature, fixed	90 °C
Number of cores	4
Class	Ordinary duty
With earthing	Yes
Inner conductor category	Class 5 = flexible
Nominal voltage U0	0.44 kV
Core identification	Colour
Nominal voltage U	0.25 kV
Material outer sheath	PVC
Colour outer sheath	Orange
Nominal cross section conductor	1.5 mm <sup>2</sup>
Core insulation	PVC
Conductor category	Class 5 = Flexible
Conductor material	Copper

Classifications	
ETIM	EC000057
UNSPSC	26121629

Create Date:

## Disclaimer

*For use on datasheets that are created by Rexel*

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.