

Product Characteristics

Part Number: CBL1.5TWH500

CABLE TPS TWIN 1.5MM 7/050 2C 500M RED/BLACK WHITE SHEATH



Description:

Thermo-plastic sheathed cables consist of strengthened outer sheathing of PVC (polyvinyl chloride) covering individually insulated copper conductors. This cable is commonly used for residential and light commercial installations.

Attribute Name	Attribute Value
Number of cores	2
With earthing	No
Permitted cable outer temperature, fixed	90 °C
Colour outer sheath	White
Nominal voltage U0	0.75 kV
Material outer sheath	PVC
Core insulation	PVC
Core identification	Colour
Nominal cross section	1.5 mm ²
Cable height approx.	4.5 mm
Conductor category	Class 2 = Stranded
Cable width approx.	7.2 mm
Insulation thickness	0.6 mm
Nominal voltage U	0.45 kV
Earthing cable cross section	1.5 mm ²
Air temperature lower operation limit	-15 °C
Low smoke (acc. IEC 61034-2)	No
Core colour	Red,Black

Classifications	
ETIM	EC000825
UNSPSC	26121629

Create Date:

Disclaimer

For use on datasheets that are created by Rexel

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.