Product Characteristics

Part Number: CBL16SDIBKWH500

CABLE SDI 16MM 7/170 1C 500M BLACK WHITE SHEATH



Description:

Single-core, Double Insulated (SDI) cable is suitable for general wiring, unenclosed, and closed in conduit or in underground ducts. Used for domestic, commercial and industrial installations where not subject to mechanical damage.

Attribute Name	Attribute Value
Conductor category	Class 2 = Stranded
Colour outer sheath	White
Core insulation	PVC
Operating temperature	90 ℃
Material outer sheath	PVC
Outer diameter approx.	8.9 mm
Insulation thickness	2 mm
Nominal voltage U0	0.75 kV
Nominal voltage U	0.45 kV
Colour insulation	Black
Nominal cross section	16 mm ²

Classifications	
ETIM	EC000993
UNSPSC	26121629

Create Date:

Disclaimer

For use on datasheets that are created by Rexel

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.