

# Product Characteristics

**Part Number: CBL4TEBK500**

CABLE TPS 4MM 7/085 2C+E 500M RED/BLACK/EARTH BLACK SHEATH



## Description:

Thermo-plastic sheathed cables consist of strengthened outer sheathing of PVC (polyvinyl chloride) covering individually insulated copper conductors. This cable is commonly used for residential and light commercial installations.

Attribute Name	Attribute Value
Nominal voltage U	0.45 kV
Cable height approx.	6.3 mm
Nominal voltage U0	0.75 kV
Conductor category	Class 2 = Stranded
Core identification	Colour
Number of cores	2
With earthing	Yes
Cable width approx.	13.9 mm
Material outer sheath	PVC
Nominal cross section	4 mm <sup>2</sup>
Permitted cable outer temperature, fixed	90 °C
Colour outer sheath	Black
Core insulation	PVC
Insulation thickness	1.1 mm
Earthing cable cross section	2.5 mm <sup>2</sup>
Core colour	Red,Black,G/Y
Low smoke (acc. IEC 61034-2)	No
Air temperature lower operation limit	-15 °C

Classifications	
ETIM	EC000825
UNSPSC	26121629

Create Date:

## Disclaimer

*For use on datasheets that are created by Rexel*

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.