

Product Characteristics

Part Number: CBL50XLPEBK

CABLE XLPE 50MM 19/178 1C BLACK SHEATH



Description:

XLPE (Cross-Linked Polyethylene) cables. The properties of the XLPE are superior to many other insulations, offering greater strength and mechanical damage resistance. XLPE can operate in higher temperatures and higher voltages and has a longer service life than PVC.

Attribute Name	Attribute Value
Material outer sheath	PVC
Nominal cross section conductor	50 mm ²
Core insulation	XLPE
Number of cores	1
Core identification	Colour
Conductor material	Copper
Insulation thickness	2.4 mm
Stranding	19/1.78
Outer diameter approx.	12.9 mm
Conductor category	Class 2 = Stranded
Operating voltage	1000 V
Colour outer sheath	Black

Classifications	
ETIM	EC000057
UNSPSC	26121629

Create Date:

Disclaimer

For use on datasheets that are created by Rexel

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.