

# Product Characteristics

**Part Number: CBL6TEBK**

CABLE TPS 6MM 7/104 2C+E RED/BLACK/EARTH BLACK SHEATH



## Description:

Thermo-plastic sheathed cables consist of strengthened outer sheathing of PVC (polyvinyl chloride) covering individually insulated copper conductors. This cable is commonly used for residential and light commercial installations.

Attribute Name	Attribute Value
Conductor category	Class 2 = Stranded
Insulation thickness	1.1 mm
Number of cores	2
With earthing	Yes
Nominal cross section	6 mm <sup>2</sup>
Core insulation	PVC
Cable height approx.	6.9 mm
Cable width approx.	15 mm
Permitted cable outer temperature, fixed	90 °C
Core identification	Colour
Colour outer sheath	Black
Nominal voltage U	0.45 kV
Nominal voltage U0	0.75 kV
Material outer sheath	PVC
Earthing cable cross section	2.5 mm <sup>2</sup>
Low smoke (acc. IEC 61034-2)	No
Air temperature lower operation limit	-15 °C
Core colour	Red,Black,G/Y

Classifications	
ETIM	EC000825
UNSPSC	26121629

Create Date:

## Disclaimer

*For use on datasheets that are created by Rexel*

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.