



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 iCM
Product or component type	Selector switch
Device short name	ICMV
Device application	Voltmeter selector
[Ue] rated operational voltage	< 440 V AC 50/60 Hz

Complementary

[Ith] conventional free air thermal current	10 A
[Ie] rated operational current	10 A
Control type	Rotary handle 7 positions
Marking	L3L1 - L2L3 - L1L2 - 0 - L1N - L2N - L3N
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Mechanical durability	2000000 cycles
Electrical durability	1000000 cycles
Connections - terminals	Captive screw-jumper terminals <= 1.5 mm²

Environment

standards	IEC 60947-3
IP degree of protection	IP66 front face IP20 terminals
ambient air temperature for operation	-20...55 °C
ambient air temperature for storage	-25...80 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0705 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.