



### Main

Range	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
Control circuit voltage	48 V DC 48...130 V AC 50/60 Hz
9 mm pitches	2

### Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	103 mm
Width	27 mm
Depth	69 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal 1 cable(s) 2.5 mm <sup>2</sup> flexible
Wire stripping length	10 mm
Tightening torque	1 N.m

### Environment

standards	EN/IEC 60947-5-1
product certifications	ASEFA ASTA KEMA LCIE
IP degree of protection	IP20 B conforming to EN/IEC 60947-5-1 IP4 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1
overvoltage category	II
tropicalisation	2 conforming to EN/IEC 60947-5-1
relative humidity	95 % at 55 °C
ambient air temperature for storage	-40...70 °C