



Main

| | |
|-----------------------------|------------------------------------|
| Range | Acti 9 |
| Product or component type | Shunt trip release with OC contact |
| Device short name | MX + OF |
| Signal contacts composition | 1 C/O |
| Control circuit voltage | 24 V AC 50/60 Hz 24 V DC |
| 9 mm pitches | 2 |

Complementary

| | |
|--|--|
| [Ui] rated insulation voltage | 690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1 |
| [Uimp] rated impulse withstand voltage | 8 kV conforming to EN/IEC 60947-5-1 |
| Local signalling | Action indicator |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| Height | 103 mm |
| Width | 27 mm |
| Depth | 69 mm |
| Electrical durability | 10000 cycles conforming to EN/IEC 60947-5-1 |
| Connections - terminals | Plate terminal 1 cable(s) 2.5 mm ² flexible |
| Wire stripping length | 10 mm |
| Tightening torque | 1 N.m |

Environment

| | |
|-------------------------------------|---|
| standards | EN/IEC 60947-5-1 |
| product certifications | ASEFA ASTA KEMA LCIE |
| IP degree of protection | IP20 B conforming to EN/IEC 60947-5-1 IP4 conforming to EN/IEC 60947-5-1 |
| pollution degree | 3 conforming to EN/IEC 60947-5-1 |
| overvoltage category | II |
| tropicalisation | 2 conforming to EN/IEC 60947-5-1 |
| relative humidity | 95 % at 55 °C |
| ambient air temperature for storage | -40...70 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.