



Main

Range	Compact
Product name	Compact INS
Product or component type	Switch disconnector
Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	100 A AC 50/60 Hz for 220/240 V in category AC-22A 100 A AC 50/60 Hz for 380/415 V in category AC-22A 100 A AC 50/60 Hz for 440/480 V in category AC-22A 100 A AC 50/60 Hz for 500 V in category AC-22A 100 A AC 50/60 Hz for 660/690 V in category AC-22A 100 A AC 50/60 Hz for 220/240 V in category AC-23A 100 A AC 50/60 Hz for 380/415 V in category AC-23A 100 A AC 50/60 Hz for 440/480 V in category AC-23A 100 A AC 50/60 Hz for 500 V in category AC-23A 63 A AC 50/60 Hz for 660/690 V in category AC-23A 100 A DC for 125 V in category DC-22A (2 poles in series) 100 A DC for 125 V in category DC-23A (2 poles in series)
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	100 A (60 °C)
[Icm] rated short-circuit making capacity	154 kA 690 V AC 50/60 Hz with upstream protection circuit breaker 20 kA 690 V AC 50/60 Hz switch-disconnector alone
[Ue] rated operational voltage	125 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Complementary

Control type	Rotary handle
Handle colour	Black
Mounting mode	Fixed
Mounting support	DIN rail Plate
Upside connection	Front
Downside connection	Front
Maximum power	22 kW AC 50/60 Hz for 220/240 V in category AC-23 45 kW AC 50/60 Hz for 380/415 V in category AC-23 55 kW AC 50/60 Hz for 440 V in category AC-23 55 kW AC 50/60 Hz for 500/525 V in category AC-23 55 kW AC 50/60 Hz for 660/690 V in category AC-23

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
Enclosure dimensions for Ithe	260 mm x 160 mm x 55 mm
[Icw] rated short-time withstand current	0.01 kA (30 s) conforming to IEC 60947-3 1.23 kA (20 s) conforming to IEC 60947-3 3.175 kA (3 s) conforming to IEC 60947-3 5.5 kA (1 s) conforming to IEC 60947-3
Mechanical durability	15000 cycles
Electrical durability	1500 cycles for 220/240 V AC 50/60 Hz in catagory AC-22A 1500 cycles for 380/415 V AC 50/60 Hz in catagory AC-22A 1500 cycles for 440 V AC 50/60 Hz in catagory AC-22A 1500 cycles for 500 V AC 50/60 Hz in catagory AC-22A 1500 cycles for 690 V AC 50/60 Hz in catagory AC-22A 1500 cycles for 220/240 V AC 50/60 Hz in catagory AC-23A 1500 cycles for 380/415 V AC 50/60 Hz in catagory AC-23A 1500 cycles for 440 V AC 50/60 Hz in catagory AC-23A 1500 cycles for 500 V AC 50/60 Hz in catagory AC-23A 1500 cycles for 690 V AC 50/60 Hz in catagory AC-23A 1500 cycles for 250 V DC in catagory DC-22A (2 poles in series) 1500 cycles for 250 V DC in catagory DC-23A (2 poles in series)
Connection pitch	30 mm
Height	100 mm
Width	135 mm
Depth	62.5 mm
Product weight	0.8 kg

Environment

standards	IEC 60947-1 IEC 60947-3
product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C