



### Main

Range of product	INS250
Range	Compact
Device short name	INS250
Product or component type	Changeover switch
Device application	Change source of supply
Range compatibility	Compact - Compact INS INS250 switch disconnecter
Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
Mounting mode	Fixed
Upside connection	Front
Downside connection	Front
Suitability for isolation	Yes
Contact position indicator	Yes
[Icm] rated short-circuit making capacity	30 kA 690 V AC 50/60 Hz switch-disconnector alone 330 kA 690 V AC 50/60 Hz with upstream protection circuit breaker

### Complementary

Transfer switch class	PC
Number of contact position	3
Control type	Direct front rotary handle
Mounting support	Plate Rail
Locking options description	Padlocking in OFF position
[Ie] rated operational current	AC-23A : 250 A AC 50/60 Hz 220/240 V AC-22A : 250 A AC 50/60 Hz 440/480 V AC-23A : 250 A AC 50/60 Hz 500/525 V AC-22A : 250 A AC 50/60 Hz 220/240 V AC-22A : 250 A AC 50/60 Hz 500/525 V AC-23A : 250 A AC 50/60 Hz 380/415 V AC-22A : 250 A AC 50/60 Hz 380/415 V DC-22A : 250 A DC 125 V 2 poles in series AC-23A : 250 A AC 50/60 Hz 480 V NEMA AC-22A : 250 A AC 50/60 Hz 480 V NEMA AC-23A : 250 A AC 50/60 Hz 440/480 V DC-23A : 250 A DC 125 V 2 poles in series AC-23A : 250 A AC 50/60 Hz 660/690 V AC-22A : 250 A AC 50/60 Hz 660/690 V
[Ith] conventional free air thermal current	250 A ( 60 °C )
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ue] rated operational voltage	125 V DC conforming to IEC 60947-3 690 V AC 50/60 Hz conforming to IEC 60947-3 750 V AC 50/60 Hz conforming to IEC 60947-3 750 V DC conforming to IEC 60947-3
Mechanical interlocking	With mechanical interlocking
Mechanical durability	15000 cycles
Electrical durability	AC-22A : 15000 cycles 440 V AC 50/60 Hz

AC-22A : 1500 cycles 500 V AC 50/60 Hz  
 AC-22A : 1500 cycles 690 V AC 50/60 Hz  
 AC-23A : 1500 cycles 440 V AC 50/60 Hz  
 AC-23A : 1500 cycles 500 V AC 50/60 Hz  
 AC-23A : 1500 cycles 690 V AC 50/60 Hz  
 DC-22A : 1500 cycles 125 V DC 2 poles in series  
 DC-23A : 1500 cycles 125 V DC 2 poles in series

Connection pitch	45 mm
[Icw] rated short-time withstand current	1.8 kA ( 30 s ) conforming to IEC 60947-3 2.2 kA ( 20 s ) conforming to IEC 60947-3 4.9 kA ( 3 s ) conforming to IEC 60947-3 8.5 kA ( 1 s ) conforming to IEC 60947-3
Height	136 mm
Width	295 mm
Depth	131 mm
Product weight	6.4 kg

## Environment

standards	IEC 60947-1 IEC 60947-3
product certifications	CCC KEMA-KEUR
electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60947-3
pollution degree	3
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C