



Main

Device short name	MN
Product or component type	Voltage release
Device application	Control
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600 Masterpact Masterpact NT Masterpact Masterpact NT NAVY Compact Masterpact NW Compact Masterpact NW NAVY
Offer type	C4 C5
Voltage release type	Undervoltage release
Control circuit voltage	200...250 V DC 200...250 V AC

Complementary

Threshold tripping voltage	0.35...0.7 Un - during opening time 0.85 Un - during closing time
Supply holding power	4.5 VA
Mounting mode	Fixed
Response time	40 ms Masterpact NT 90 ms Masterpact NW
Accessory / separate part category	Spare parts Masterpact NT Spare parts Masterpact NW Spare parts Compact NS1600b...3200 Spare parts Compact NS630b...1600

Environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.