



Main

| | |
|---------------------------|-----------------|
| Range of product | Harmony 9001SK |
| Product or component type | Selector switch |
| Device short name | 9001SK |

Complementary

| | |
|---------------------|---------------|
| Bezel material | Plastic |
| Mounting diameter | 30 mm |
| Device presentation | Basic element |

Environment

| | |
|--|---|
| protective treatment | TC |
| ambient air temperature for storage | -40...70 °C |
| ambient air temperature for operation | -25...70 °C |
| class of protection against electric shock | Class II conforming to IEC 61140 |
| IP degree of protection | IP66 conforming to IEC 60529 |
| NEMA degree of protection | NEMA 1/2/3/3R/4/4X/6/12/13 |
| product certifications | CE UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03 |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | 785901959878 |
| RoHS (date code: YYWW) | Compliant - since 0921 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.