



Main

Range	TeSys
Product name	TeSys CAD
Product or component type	Control relay
Device short name	CAD
Contactors application	Control circuit

Complementary

Utilisation category	AC-14 AC-15 DC-13
Pole contact composition	3 NO + 2 NC
[Ue] rated operational voltage	≤ 690 V AC 25...400 Hz
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	120 V DC
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
[Ith] conventional free air thermal current	10 A at ≤ 60 °C
Irms rated making capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
[Icw] rated short-time withstand current	100 A 1 s 120 A 500 ms 140 A 100 ms
Associated fuse rating	10 A gG conforming to IEC 60947-5-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1 600 V certifications UL 600 V certifications CSA
Mounting support	Plate Rail
Connections - terminals	Screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end
Tightening torque	1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Control circuit voltage limits	0.3...0.6 U _c drop-out 0.8...1.1 U _c operational 50 Hz 0.85...1.1 U _c operational 60 Hz
Operating time	4...19 ms coil energisation and NC opening 12...22 ms coil energisation and NO closing 4...12 ms coil de-energisation and NO opening 6...17 ms coil de-energisation and NC closing
Mechanical durability	30 Mcycles
Operating rate	180 cyc/mn
Inrush power in VA	70 VA at 20 °C 50 Hz
Hold-in power consumption in VA	8 VA at 20 °C 50 Hz
Minimum switching voltage	17 V
Minimum switching current	5 mA

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Non-overlap time	1.5 ms on de-energisation (between NC and NO contact) 1.5 ms on energisation (between NC and NO contact)
Insulation resistance	> 10 MOhm
Mechanical robustness	Shocks control relay open 10 Gn for 11 ms IEC 60068-2-27 Shocks control relay closed 15 Gn for 11 ms IEC 60068-2-27 Vibrations control relay open 2 Gn, 5...300 Hz IEC 60068-2-6 Vibrations control relay closed 4 Gn, 5...300 Hz IEC 60068-2-6
Height	77 mm
Width	45 mm
Depth	84 mm
Product weight	0.58 kg

Environment

standards	VDE 0660 IEC 60947-5-1 NF C 63-140 BS 4794 EN 60947-5
product certifications	CSA UL
IP degree of protection	IP2x front face conforming to VDE 0106
protective treatment	TH conforming to IEC 60068
ambient air temperature for operation	-40...70 °C
ambient air temperature for storage	-60...80 °C
operating altitude	3000 m without derating in temperature

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available