


LA4DWB

TeSys D - interface amplifier module - solid state -
24 V DC / 250 V AC



Main

Range	TeSys
Device short name	LA4D
Poles description	3P
Product or component type	Interface module
Product compatibility	LC1D09...D115

Complementary

Mounting mode	Top mounted
Technology type	Solid state
[Us] rated supply voltage	24 V DC
Control circuit voltage limits	5...30 V at 20 °C DC
[Ui] rated insulation voltage	250 V - for control circuit - conforming to IEC 60947-5-1
Connections - terminals	Control circuit : connector 2 cable 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit : connector 2 cable 1...2.5 mm ² - cable stiffness: flexible - without cable end Control circuit : connector 1 cable 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit : connector 1 cable 1...2.5 mm ² - cable stiffness: flexible - without cable end Control circuit : connector 1 cable 1...2.5 mm ² - cable stiffness: solid - with cable end Control circuit : connector 1 cable 1...2.5 mm ² - cable stiffness: solid - without cable end Control circuit : connector 2 cable 1...2.5 mm ² - cable stiffness: solid - with cable end Control circuit : connector 2 cable 1...2.5 mm ² - cable stiffness: solid - without cable end
[Ue] rated operational voltage	380...415 V AC for control circuit 24...250 V AC for control circuit
Current consumption	8.5...15 mA 20 °C
Current state 0 guaranteed	<= 2 mA
Voltage state 0 guaranteed	< 2.4 V
Voltage state 1 guaranteed	5 V
Electrical durability	20 Mcycles at 240 V
Local signalling	LED indicator
Height	19 mm
Product weight	0.045 kg

Environment

standards	IEC 60255-5
product certifications	CSA UL
protection type	Built-in by diode
IP degree of protection	IP2x conforming to VDE 0106
protective treatment	TH conforming to IEC 60068
ambient air temperature for operation	-25...55 °C
permissible ambient air temperature around the device	-25...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

ambient air temperature for storage	-40...80 °C
heat dissipation	0.4 W for control circuit
immunity to microbreaks	1 ms

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0850 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations