



## Main

|                           |                   |
|---------------------------|-------------------|
| Range                     | TeSys             |
| Device short name         | LA4K              |
| Product or component type | Suppressor module |
| Product compatibility     | LC1<br>LP1        |

## Complementary

|                              |                |
|------------------------------|----------------|
| Mounting location            | Front side     |
| Mounting mode                | Clip-on        |
| Suppressor technology        | RC circuit     |
| [Uc] control circuit voltage | 110...250 V AC |
| Maximum peak voltage         | 3 Uc           |
| Local signalling             | LED            |
| Quantity per set             | Set of 5       |
| Height                       | 25 mm          |
| Width                        | 6 mm           |
| Depth                        | 22 mm          |
| Product weight               | 0.01 kg        |

## Environment

|                                       |  |
|---------------------------------------|--|
| standards                             | BS 5424<br>IEC 60947<br>NF C 63-110<br>VDE 0660          |
| product certifications                | CSA<br>UL  |
| IP degree of protection               | IP2x conforming to VDE 0106                              |
| protective treatment                  | TC conforming to IEC 60068<br>TC conforming to DIN 50016 |
| ambient air temperature for operation | -25...50 °C  |
| ambient air temperature for storage   | -50...80 °C  |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 0650 - Schneider Electric declaration of conformity |
| REACH                    | Reference not containing SVHC above the threshold                     |