

LR2K0316

TeSys K - differential thermal overload relays -
8...11.5 A - class 10A



Main

| | |
|-------------------------------------|---|
| Range | TeSys |
| Product name | TeSys LRK |
| Product or component type | Differential thermal overload relay |
| Device short name | LR2K |
| Relay application | Motor protection |
| Product compatibility | LC1K LP1K LC7K LP4K |
| Network type | AC DC |
| Thermal overload class | Class 10A conforming to IEC 60947-4-1 |
| Thermal protection adjustment range | 8...11.5 A |
| [Ui] rated insulation voltage | 690 V power circuit conforming to BS 4941 690 V power circuit conforming to IEC 60947 750 V power circuit conforming to VDE 0110 group C 600 V power circuit conforming to CSA C22.2 No 14 |

Complementary

| | |
|---|--|
| Network frequency | <= 400 Hz |
| Mounting support | Plate with specific accessories Rail with specific accessories Under contactor |
| Auxiliary contact composition | 1 NO + 1 NC |
| [Ith] conventional free air thermal current | 6 A for signalling circuit |
| [Ue] rated operational voltage | <= 690 V for power circuit 690 V AC AC-15 for signalling circuit 250 V DC DC-13 for signalling circuit |
| Associated fuse rating | 6 A gG for signalling circuit conforming to VDE 0660 6 A gG for signalling circuit conforming to IEC 60947 |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Power dissipation per pole | 2 W |
| Phase failure sensitivity | Yes conforming to IEC 60947-4-1 |
| Local signalling | Trip indicator (yellow) |
| Control type | Selector switch manual or automatic for reset mode Red push-button trip test function Blue push-button stop and manual reset |
| Connections - terminals | Screw clamp terminals 1 cable(s) 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable(s) 0.75...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 0.34...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 2 cable(s) 0.75...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² - cable stiffness: flexible - with cable end |
| Tightening torque | 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm |
| Height | 58 mm |
| Width | 45 mm |
| Depth | 65 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|----------------|----------|
| Product weight | 0.145 kg |
|----------------|----------|

Environment

| | |
|---------------------------------------|--|
| standards | BS 4941 IEC 60947 NF C 63-650 VDE 0660 |
| product certifications | CSA UL |
| protective treatment | TC conforming to IEC 60068 TC conforming to DIN 50016 |
| IP degree of protection | IP2x conforming to IEC 60529 |
| ambient air temperature for operation | -20...55 °C without derating conforming to IEC 60947 -30...60 °C with derating conforming to IEC 60947 |
| ambient air temperature for storage | -40...70 °C |
| operating altitude | 2000 m without derating |
| fire resistance | 850 °C conforming to IEC 60695-2-1 |
| flame retardance | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |
| mechanical robustness | Shocks NO contact 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks NC contact 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations NO contact 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations NC contact 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0701 - Schneider Electric declaration of conformity |
| REACH | Reference contains SVHC above the threshold |