



## Main

Range	TeSys
Product name	TeSys LRD
Product or component type	Electronic thermal overload relay
Device short name	LR9D
Relay application	Motor protection
Product compatibility	LC1D115 LC1D150 NSX circuit breaker
Network type	AC
Signalling function	Alarm
Thermal protection adjustment range	90...150 A
[Ui] rated insulation voltage	1000 V power circuit conforming to IEC 60947-4-1 600 V power circuit conforming to CSA 600 V power circuit conforming to UL

## Complementary

Network frequency	50...60 Hz
[Us] rated supply voltage	24 V DC
Supply voltage limits	17...32 V
Mounting support	Rail Under contactor
Tripping threshold	1.05 +/- 0.06 In alarm conforming to IEC 60947-4-1 1.12 +/- 0.06 In de-energisation conforming to IEC 60947-4-1
[Ith] conventional free air thermal current	5 A for signalling circuit
[Ue] rated operational voltage	690 V 50...60 Hz
Associated fuse rating	5 A gG for signalling circuit
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 61000-4-5
Phase failure sensitivity	Tripping in 4 s +/- 20 % conforming to IEC 60947-4-1
Control type	Red push-button stop Blue push-button for reset mode
Temperature compensation	-20...60 °C
Switching capacity in mA	0...150 mA
Voltage drop	<= 2.5 V closed state
Connections - terminals	Power circuit : bars Control circuit : screw clamp terminals 1 cable(s) 0.5...1.5 mm <sup>2</sup> flexible without cable end Control circuit : screw clamp terminals 2 cable(s) 0.5...1.5 mm <sup>2</sup> flexible without cable end Alarm circuit : screw clamp terminals 1 cable(s) 0.5...1.5 mm <sup>2</sup> flexible without cable end
Tightening torque	Alarm circuit : 0.45 N.m on screw clamp terminals Power circuit : 18 N.m on bars screw : M8 Control circuit : 1.2 N.m on screw clamp terminals
Depth	132 mm
Product weight	0.9 kg

## Environment

protective treatment	TH conforming to IEC 60068
IP degree of protection	IP20 conforming to IEC 60529

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

ambient air temperature for operation	-20...60 °C without derating conforming to IEC 60947-4-1
ambient air temperature for storage	-60...70 °C
operating altitude	<= 2000 m without derating
mechanical robustness	Vibrations 2 Gn, 5...300 Hz IEC 60068-2-6 Shocks 13 Gn for 11 ms IEC 60068-2-7
dielectric strength	6 kV at 50 Hz conforming to IEC 60255-5
standards	EN 60947-4-1 IEC 255-17 IEC 255-8 IEC 60947-4-1 VDE 0660
product certifications	CSA 22-2 UL 508

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available