



### Main

Range	TeSys
Device short name	LUA
Product or component type	Limiter disconnecter

### Complementary

Product compatibility	LU2B LUB
[Ith] conventional free air thermal current	32 A
Breaking capacity	70 kA at 690 V 130 kA
Mounting mode	Direct
[Ui] rated insulation voltage	690 V conforming to EN 60947-1 690 V conforming to IEC 60947-1
Irms rated making capacity	50 kA
Connections - terminals	Connector 1 cable 1...10 mm <sup>2</sup> - cable stiffness: flexible - without cable end Connector 1 cable 1...6 mm <sup>2</sup> - cable stiffness: flexible - with cable end Connector 1 cable 1.5...10 mm <sup>2</sup> - cable stiffness: solid - Connector 2 cable 1...6 mm <sup>2</sup> - cable stiffness: flexible - with cable end Connector 2 cable 1...6 mm <sup>2</sup> - cable stiffness: flexible - without cable end Connector 2 cable 1.5...6 mm <sup>2</sup> - cable stiffness: solid -
Tightening torque	1.9...2.5 N.m (flat Ø 6 mm screwdriver) 1.9...2.5 N.m (Philips No 2 screwdriver)
Product weight	0.31 kg

### Environment

#### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1826 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations