

LUFP7
Profibus DP/Modbus communication gateway - 1
Profibus DP SUB-D9 - 1 RJ45 Modbus



Main

Range	TeSys
Device short name	LUF
Product or component type	Communication gateway
Product compatibility	ATS48 ATV31 TeSys U starter-controllers

Complementary

Bus type	Modbus Profibus DP
Connector type	Female SUB-D 9 field bus RJ45 Modbus RJ45 to a PC
Maximum number of connections	<= 8 Modbus slaves
[Us] rated supply voltage	24 V DC +/- 10 %
Current consumption	100 mA typical 280 mA maximum
Local signalling	LED front panel
Services	Command - bus type: Profibus DP - functions available: 122 configurable words Configuration and adjustment - bus type: Fipio - functions available: by gateway mini messaging facility Monitoring - bus type: Profibus DP - functions available: 122 configurable words
Product weight	0.245 kg

Environment

electromagnetic compatibility	Electromagnetic emission conforming to IEC 50081-2 Electromagnetic immunity conforming to IEC 61000-6-2
pollution degree	2 conforming to IEC 60664
ambient air temperature for installation	5...50 °C
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company Schneider Electric. This information is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.