



Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1FG
Range compatibility	TeSys F LC1F contactor
Product compatibility	LC1F185 LC1F225
Control circuit type	AC 50 Hz
[Uc] control circuit voltage	24 V AC 50 Hz
Average resistance	0.18 Ohm at 20 °C
Inductance of closed circuit	0.03 H
Operating time	20...35 ms closing 7...15 ms opening
Mechanical durability	10 Mcycles
Operating rate	<= 2400 cyc/h at <= 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.85...1.1 Uc at 55 °C operational 50/60 Hz 0.35...0.55 Uc at 55 °C drop-out 50/60 Hz
Inrush power in VA	805 VA at 20 °C (cos f 0.3) 50 Hz
Hold-in power consumption in VA	55 VA at 20 °C (cos f 0.3) 50 Hz
Heat dissipation	18...24 W at 50 Hz

Environment

ambient air temperature for operation	> -5...55 °C
product weight	0.55 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0830 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available