

VCD0

switch-disconnector VCD - TeSys - 3 poles -
690 V 25 A - padlockable red handle



Main

Range of product	TeSys VARIO
Device short name	Main switch disconnector
Product or component type	Rotary switch disconnector
Switch function	Emergency stop
Poles description	3P
Network type	AC
Handle colour	Red
Handle front plate colour	Yellow
Mounting support	Door, diameter : 22.5 mm
[Ith] conventional free air thermal current	25 A
Suitability for isolation	Yes

Complementary

Kit composition	V0 switch body Red handle
Control type	With emergency stop
Rotary handle padlocking	Upto 3 padlocks
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ithe] conventional enclosed thermal current	20 A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[I_e] rated operational current

0,5 A 220 V L/R = 1 ms DC-4 1
0,5 A 250 V L/R = 1 ms DC-4 1
0,5 A 220 V L/R = 1 ms DC-5 1
0,5 A 250 V L/R = 1 ms DC-5 1
0,5 A 220 V L/R = 1 ms DC-2 1
0,5 A 250 V L/R = 1 ms DC-2 1
0,5 A 220 V L/R = 1 ms DC-3 1
0,5 A 250 V L/R = 1 ms DC-3 1
0,8 A 250 V L/R = 1 ms DC-4 2
0,8 A 250 V L/R = 1 ms DC-5 2
0,8 A 250 V L/R = 1 ms DC-1 1
0,8 A 250 V L/R = 1 ms DC-2 2
0,8 A 250 V L/R = 1 ms DC-3 2
1,5 A 220 V L/R = 1 ms DC-4 2
1,5 A 220 V L/R = 1 ms DC-5 2
1,5 A 220 V L/R = 1 ms DC-2 2
1,5 A 220 V L/R = 1 ms DC-3 2
1,6 A 250 V L/R = 1 ms DC-4 3
1,6 A 250 V L/R = 1 ms DC-5 3
1,6 A 250 V L/R = 1 ms DC-2 3
1,6 A 250 V L/R = 1 ms DC-3 3
2,5 A 110 V L/R = 1 ms DC-4 1
2,5 A 110 V L/R = 1 ms DC-5 1
2,5 A 220 V L/R = 1 ms DC-1 1
2,5 A 110 V L/R = 1 ms DC-2 1
2,5 A 110 V L/R = 1 ms DC-3 1
3 A 220 V L/R = 1 ms DC-4 3
3 A 220 V L/R = 1 ms DC-5 3
3 A 220 V L/R = 1 ms DC-2 3
3 A 220 V L/R = 1 ms DC-3 3
5 A 110 V L/R = 1 ms DC-4 2
5 A 110 V L/R = 1 ms DC-5 2
5 A 110 V L/R = 1 ms DC-2 2
5 A 110 V L/R = 1 ms DC-3 2
6 A 250 V L/R = 1 ms DC-1 2
9 A 110 V L/R = 1 ms DC-1 1
10 A 220 V L/R = 1 ms DC-1 2
12 A 110 V L/R = 1 ms DC-1 2
12 A 250 V L/R = 1 ms DC-1 3
14 A 415 V AC-23A
14,5 A 400 V AC-23A
16 A 60 V L/R = 1 ms DC-5 1
16 A 220 V L/R = 1 ms DC-1 3
16 A 60 V L/R = 1 ms DC-2 1
16 A 60 V L/R = 1 ms DC-3 1
16 A 60 V L/R = 1 ms DC-4 1
16,7 A 500 V AC-23A
17,5 A 690 V AC-23A
19,7 A 230 V AC-23A
19,9 A 240 V AC-23A
25 A 230...690 V AC-21A
25 A 60 V L/R = 1 ms DC-4 2
25 A 60 V L/R = 1 ms DC-4 3
25 A 110 V L/R = 1 ms DC-4 3
25 A 24 V L/R = 1 ms DC-5 1
25 A 24 V L/R = 1 ms DC-5 2
25 A 24 V L/R = 1 ms DC-5 3
25 A 48 V L/R = 1 ms DC-5 1
25 A 48 V L/R = 1 ms DC-5 2
25 A 48 V L/R = 1 ms DC-5 3
25 A 60 V L/R = 1 ms DC-5 2
25 A 60 V L/R = 1 ms DC-5 3
25 A 110 V L/R = 1 ms DC-5 3
25 A 230...690 V AC-22A
25 A 24 V L/R = 1 ms DC-1 1
25 A 24 V L/R = 1 ms DC-1 2
25 A 24 V L/R = 1 ms DC-1 3
25 A 48 V L/R = 1 ms DC-1 1
25 A 48 V L/R = 1 ms DC-1 2
25 A 48 V L/R = 1 ms DC-1 3
25 A 60 V L/R = 1 ms DC-1 1
25 A 60 V L/R = 1 ms DC-1 2
25 A 60 V L/R = 1 ms DC-1 3
25 A 110 V L/R = 1 ms DC-1 3
25 A 24 V L/R = 1 ms DC-2 1
25 A 24 V L/R = 1 ms DC-2 2
25 A 24 V L/R = 1 ms DC-2 3
25 A 48 V L/R = 1 ms DC-2 1
25 A 48 V L/R = 1 ms DC-2 2
25 A 48 V L/R = 1 ms DC-2 3
25 A 60 V L/R = 1 ms DC-2 2
25 A 60 V L/R = 1 ms DC-2 3
25 A 110 V L/R = 1 ms DC-2 3
25 A 24 V L/R = 1 ms DC-3 1
25 A 24 V L/R = 1 ms DC-3 2

Rated operational power in W	4 W 230...240 V AC-3 5,5 W 400...415 V AC-3 5,5 W 230 V AC-23A 5,5 W 240 V AC-23A 7,5 W 500 V AC-3 7,5 W 400 V AC-23A 7,5 W 415 V AC-23A 11 W 690 V AC-3 11 W 500 V AC-23A 15 W 690 V AC-23A
Intermittent duty class	30
Making capacity	250 A 400 V AC-21A 250 A 400 V AC-22A 250 A 400 V AC-23A
[Icm] rated short-circuit making capacity	1 kA 400 V at Ipeak
[Icw] rated short-time withstand current	300 kA 400 V 1 s
Rated conditional short-circuit current	10 kA 400 V 25 A aM 10 kA 400 V 25 A gG
Breaking capacity	200 kA 400 V AC-21A 200 kA 400 V AC-22A 200 kA 400 V AC-23A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles DC-1...5 100000 cycles AC-21
Connections - terminals	Screw terminals power circuit 6 mm ² flexible with Screw terminals power circuit 10 mm ² solid
Tightening torque	2,1 N.m power circuit screw terminals
Provision for padlocking	Padlockable
Marking	0 - 1
Base dimension	60 x 60 mm
Product weight	0,215 kg

Environment

Standards	IEC 60947-3
Product certifications	CCC CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 with protection shrouds IEC 60529 IP65
Shock resistance	30 gn IEC 60068-2-27
Vibration resistance	1 gn IEC 60068-2-6
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C IEC 60695-2-1
RoHS EUR conformity date	0733
RoHS EUR status	Compliant