



Main

| | |
|-------------------------------|------------------------------------|
| Range | TeSys |
| Product name | TeSys VARIO |
| Device short name | VCD |
| Product or component type | Emergency stop switch disconnecter |
| Performance level | High performance |
| Poles description | 3P |
| Contacts type and composition | 3 NO |
| Network type | AC DC |
| Control type | Rotary handle |
| Rotary handle mounting style | Direct |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Suitability for isolation | Yes |

Complementary

| | |
|--|--|
| Rotary handle padlocking | 1 to 3 padlocks 4...8 mm |
| Marking | 0 - 1 |
| Mounting support | Handle mounting on door Switch mounting on door |
| Fixing mode | Hole with 22.5 mm for handle |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ith] conventional free air thermal current | 40 A |
| [Ithe] conventional enclosed thermal current | 32 A |
| [Ie] rated operational current | 29 A (AC-23) at 400 V |
| Rated operational power in W | 11 kW at 400...415 V (AC-3) 11 kW at 690 V (AC-3) 15 kW at 500 V (AC-3) 15 kW at 690 V (AC-23A) 18.5 kW at 500 V (AC-23A) 5.5 kW at 230...240 V (AC-3) 7.5 kW at 230...240 V (AC-23A) 15 kW at 400...415 V (AC-23A) |
| Intermittent duty class | 30 |
| Making capacity | 400 A at 400 V (AC-21A) 400 A at 400 V (AC-22A) 400 A at 400 V (AC-23A) |
| [Icm] rated short-circuit making capacity | 1 kA at 400 V at Ipeak |
| [Icw] rated short-time withstand current | 480 A at 400 V during 1 s |
| Rated conditional short-circuit current | 10 kA at 400 V - associated fuse 50 A aM 10 kA at 400 V - associated fuse 50 A gG |
| Breaking capacity | 320 A at 400 V AC-21A 320 A at 400 V AC-22A 320 A at 400 V AC-23A |
| Device composition | Handle Switch |
| Mechanical durability | 100000 cycles |
| Electrical durability | 30000 cycles DC-1...5 100000 cycles AC-21 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-------------------------|---|
| Connections - terminals | Power circuit : screw clamp terminals cable 6 mm ² - cable stiffness: flexible - with cable end Power circuit : screw clamp terminals cable 10 mm ² - cable stiffness: solid |
| Tightening torque | Power circuit : 2.1 N.m - on screw clamp terminals |
| Base dimension | 60 x 60 mm |
| Height | 74 mm |
| Width | 60 mm |
| Product weight | 0.215 kg |

Environment

| | |
|---------------------------------------|--|
| standards | IEC 60947-3 |
| product certifications | CCC CSA GL UL |
| protective treatment | TC |
| IP degree of protection | IP65 IP20 conforming to IEC 60529 |
| mechanical robustness | Vibrations 10...150 Hz 1 gn IEC 60068-2-6 Shocks 11 ms 30 Gn IEC 60068-2-27 |
| ambient air temperature for operation | -20...50 °C |
| fire resistance | 960 °C conforming to IEC 60695-2-1 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0733 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |