VZ13

TeSys VARIO - additional neutral block - 175 A - for V5 / V6



Main Range

Range	TeSys
Device short name	VZ
Product or component type	Additional neutral block
Performance level	High performance
Poles description	1N
Contacts type and composition	1 NO
Contact operation	Early make, late break
Product compatibility	V5 V6
Range compatibility	TeSys VARIO switch disconnector
Network type	AC DC
Network frequency	50/60 Hz

Complementary

· · · · · · · · · · · · · · · · · · ·	
Mounting location	Left
	Right
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	175 A
Mechanical durability	30000 cycles
Electrical durability	30000 cycles DC-15
	30000 cycles AC-21
Connections - terminals	Screw clamp terminals cable 70 mm ² - cable stiffness: flexible - with cable end
	Screw clamp terminals cable 95 mm ² - cable stiffness: solid
Tightening torque	22.6 N.m - on screw clamp terminals
Height	125 mm
Width	30 mm
Depth	63 mm
Product weight	0.25 kg

Environment

standards	IEC 60947-3	
product certifications	CSA GL UL	
protective treatment	TC	
IP degree of protection	IP20 conforming to IEC 60529	
mechanical robustness	Shocks 11 ms 15 gn IEC 60068-2-27 Vibrations 10150 Hz 1 gn IEC 60068-2-6	
ambient air temperature for operation	-2050 °C	
fire resistance	960 °C conforming to IEC 60695-2-1	