XUK5APANM12

photo-electric sensor - XUK - diffuse - Sn 1m - 12..24VDC - M12



Main

| Range of product | OsiSense XU |
|-------------------------------|------------------------------|
| Series name | General purpose single mode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUK |
| Sensor design | Compact 50 x 50 |
| Detection system | Diffuse |
| Material | Plastic |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Wiring technique | 3-wire |
| Discrete output type | PNP |
| Discrete output function | 1 NO |
| Electrical connection | 1 male connector M12, 4 pins |
| Product specific application | - |
| Emission | Infrared diffuse |
| [Sn] nominal sensing distance | 1 m diffuse |

Complementary

| Complementary | | |
|---------------------------|---------------------------------------------------|---|
| Enclosure material | PBT | |
| Lens material | РММА | |
| Maximum sensing distance | 1.5 m diffuse | |
| Output type | Solid state | |
| Wire insulation material | PVC | _ |
| Status LED | 1 LED (yellow) for output state | _ |
| [Us] rated supply voltage | 1224 V DC | |
| Switching capacity in mA | <= 100 mA (overload and short-circuit protection) | |
| Switching frequency | <= 250 Hz | |
| Voltage drop | <= 1.5 V (closed state) | |
| Current consumption | <= 35 mA (no-load) | |
| Delay first up | < 15 ms | |
| Delay response | < 2 ms | |
| Delay recovery | < 2 ms | |
| Setting-up | Without sensitivity adjustment | |
| Depth | 50 mm | |
| Height | 50 mm | |
| Width | 18 mm | |
| Product weight | 0.19 kg | |
| | | |


Environment

| product certifications | CE CSA UL | |
|---------------------------------------|------------------------------------------------------------------------|--|
| ambient air temperature for operation | -2555 °C | |
| ambient air temperature for storage | -4070 °C | |
| vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6 | |
| shock resistance | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27 | |
| IP degree of protection | IP65 double insulation conforming to IEC 60529 | |

Offer Sustainability


| Sustainable offer status | Not Green Premium product |
|--------------------------|-----------------------------------------------------------------------|
| RoHS (date code: YYWW) | Compliant - since 0841 - Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold |

Dimensions




Mounting and Clearance

Possible Orientation of Elbowed Connector



Wiring Schemes


M12 Connector




1: (+) 3: (-)

4: OUT/Output

PNP Outputs



Detection Curves



2: Grey 18%
Object 10 x 10 cm