

XVBC21A

Ø 70 mm base unit + cover - with AS-i connection - black



Main

Range of product	Harmony XVB Universal
Product or component type	Base unit with cover
Component name	XVBC

Complementary

Range compatibility	AS-Interface cabling system
Material	Glass reinforced polyamide on base unit Polycarbonate on cover unit
Mounting diameter	70 mm
[Us] rated supply voltage	19.2...30 V for external application 24...31.6 V for AS-Interface line application
Current consumption	30 mA (no load) 250 mA (under load) via AS-Interface line 30 mA (under load) external
Actuator sensor interface profile [AS-i]	S.7.F
Electrical connection	1 connector M12 for AS-Interface line
Cable entry	Side entry
Assembly style	Customer assembly, up to 5 units
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1
Terminals description ISO n°1	(COM-1)PW (COM-2)PW (COM-3)PW (COM-4)PW (COM-5)PW (GND)GROUND
Product weight	0.19 kg

Environment


product certifications	AS-Interface No 25701 CSA
standards	EN/IEC 60947-5-1
protective treatment	TC
ambient air temperature for storage	-20...70 °C
ambient air temperature for operation	-10...50 °C
shock resistance	25 gn conforming to IEC 60068-2-27
vibration resistance	5 gn conforming to IEC 60068-2-6
overvoltage category	Class I conforming to IEC 60536
IP degree of protection	IP65 conforming to IEC 60529 IP65 conforming to NF C 20-010
NEMA degree of protection	NEMA 4X indoor conforming to UL 508

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Indicator Bank without “Flash” Discharge Tube Unit

Dimensions

Below drawing shows the minimum configuration of the product. Select the number of stages according to the product characteristics in order to get **b** dimension.




- (1) Base unit
- (2) Illuminated or audible signalling unit XVBC•••, to be ordered separately
- (3) Cover (supplied with base unit)

Number of illuminated or audible signalling units (no “flash”)	b in mm	b in in.
1	138	5.43
2	201	7.91
3	264	10.39
4	327	12.87

Base Unit for Indicator Banks

Panel Cut-out for Direct Fixing



Illuminated Beacon

Wiring Diagram

