

## ZBZG156

single light block for test light function 12V



### Main

Range of product	Harmony XB4 Harmony XB5
Product or component type	Block for test light
Product compatibility	BA 9s Integral LED
Light block type	Single block for test light function
[Us] rated supply voltage	12 V AC/DC 24 V AC/DC 24...120 V AC/DC
Electrical connection	1 wire

### Complementary

Electrical shock protection class	Class I for Harmony XB4 conforming to IEC 60536 Class II for Harmony XB5 conforming to IEC 60536
Product weight	0.01 kg

### Environment

ambient air temperature for storage	-40...70 °C
ambient air temperature for operation	-25...70 °C
standards	EN 60947-1 EN 60947-5-1 EN 60947-5-4 EN 60947-5-5 IEC 60947-1 IEC 60947-5-1 IEC 60947-5-4 IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
product certifications	BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed
vibration resistance	5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6
shock resistance	30 gn for 18 ms conforming to IEC 60068-2-27 50 gn for 11 ms conforming to IEC 60068-2-27

### Wiring Diagram

