

Product data sheet

Characteristics

PBELKIT2PB

Emergency Light Kit, Acti9, 2 N/C, Push Button

Main

| | |
|------------------------------------|--|
| Range of the product | Acti9 |
| Product or component type | Emergency light test kit |
| Device application | Emergency lighting |
| Accessory / separate part category | Enclosure accessory |
| Provided equipment | 1 contactor 1 relay 2 push buttons 1 DIN rail |

Complementary

| | |
|-------------------------------|------------------------------------|
| [In] rated current | 25 A |
| Rated voltage | 230...240 V AC |
| Control type | 1 push-button |
| Pole contact composition | 4 NC |
| Time delay | 0.1...10 h Factory set to 2 hrs |
| Total number of 18 mm modules | 4 |
| Connections - terminals | Cable with cable end |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 22.9 cm |
| Package 1 Width | 19.7 cm |
| Package 1 Length | 19.0 cm |
| Package 1 Weight | 496.0 g |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.