

SHP/SHP-T/LU Standard

High Pressure Sodium Features exclusive frameless construction for improved reliability with fewer early failures. This range provide a large wattage range with either clear tubular or coated ellipsoidal outer bulb. Delivering a pleasant golden white light gives a warm colour appearance, the range is ideal for major applications in road lighting, both on motorways and in residential streets and is an excellent choice for general industrial lighting, both indoors and for outdoor floodlighting. Requires external lamp ignition and ballast



- SHP/SHP-T/LU Standard
- Large wattage range with either clear tubular or coated ellipsoidal outer bulb
- Pleasant golden white light gives a warm colour appearance





4
CRI



1 Years
Warranty

CODE	LAMP POWER	EXIT LUMEN	CCT	DIMENSIONS	VOLTAGE
205180	1000W	130000lm	2050K	L400 x W68 x H68 mm	100V
672040	400W	48000lm	2050K	L292 x W48 x H48 mm	105V
672060	250W	28000lm	2050K	L260 x W48 x H48 mm	100V
672070	250W	27000lm	2050K	L227 x W91 x H91 mm	100V
673140	150W	14500lm	2050K	L221 x W48 x H211 mm	100V
673150	150W	14000lm	2050K	L227 x W91 x H91 mm	100V
673260	70W	5800lm	2050K	L165 x W72 x H72 mm	90V



	50W	70W	100W	150W	250W	400W
SHP						
L	165	165	178	227	227	292
D	72	72	78	91	91	122
SHP-T						
L	156	156	-	211	260	292
D	39	39	-	48	48	68
LU	1000W					
L	385					
D	80					

*Rated LED design life where stated is based upon application of Pierlite's operating and maintenance guidelines; see pierlite.com.au. Actual product life may vary dependent upon frequency of maintenance and product application. Due to continual product improvement, information is subject to change without notification. Pierlite standard Terms and Conditions apply.