



Main

Accessory / separate part category	Mounting accessories
Accessory / separate part type	Notched uprights
Enclosure accessory description	Notched mounting rail
Quantity per set	Set of 2 Set of 4
Star-delta starter component	Mounting rails Uprights

Complementary

Assembly style	For assembly
Depth	25 mm
Height	0 mm 2000 mm
Horizontal fixing centres	1550 mm
Length	2000 mm
Material	Steel coated with zinc chromate
Motor power kW	90...375 kW
Motor starter type	Star-delta starters
Number of devices	2 1
Product compatibility	For enclosure of width 1600 mm For enclosure of height 1600 mm
Product weight	2.4 kg 2.98 kg
Type of rail	Notched
Surface treatment	Zinc chromate
Thickness	2 mm
Vertical fixing centres	1500 mm
Width	0 mm 1600 mm 40 mm

Environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.