



Main

| | |
|---------------------------|-------------------|
| Range | TeSys |
| Device short name | LA4K |
| Product or component type | Suppressor module |
| Product compatibility | LC1 LP1 |

Complementary

| | |
|------------------------------|------------------------------|
| Mounting location | Front side |
| Mounting mode | Clip-on |
| Suppressor technology | Varistor (peak limiting) |
| [Uc] control circuit voltage | 12...24 V AC 12...24 V DC |
| Maximum peak voltage | 2 Uc |
| Local signalling | LED |
| Quantity per set | Set of 5 |
| Height | 25 mm |
| Width | 6 mm |
| Depth | 22 mm |
| Product weight | 0.01 kg |

Environment

| | |
|---------------------------------------|--|
| standards | BS 5424 IEC 60947 NF C 63-110 VDE 0660 |
| product certifications | CSA UL |
| IP degree of protection | IP2x conforming to VDE 0106 |
| protective treatment | TC conforming to IEC 60068 TC conforming to DIN 50016 |
| ambient air temperature for operation | -25...50 °C |
| ambient air temperature for storage | -50...80 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0650 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |