


## LR97D07M7

electronic overload relay for motor TeSys - 1.2...7 A  
- 200...240 V AC



### Main

Range	TeSys
Product name	TeSys D
Device short name	LR97
Product or component type	Electronic overcurrent relay
Relay application	Locked rotor, mechanical jamming $I > 3 \times I_{setting}$ Overload $I_{max} > I_{setting}$ Sensitivity to phase failure
Product compatibility	LC1D09...D38
Network type	AC
[Us] rated supply voltage	200...240 V AC
Thermal protection adjustment range	1.2...7 A
[Ue] rated operational voltage	600 V AC 50/60 Hz for power circuit conforming to CSA 600 V AC 50/60 Hz for power circuit conforming to UL 690 V AC 50/60 Hz for power circuit conforming to IEC 60947-4-1
Quantity per set	Set of 10

### Complementary

Network frequency	50...60 Hz
Mounting support	Direct on contactor Rail
Tripping threshold	1.2...6 A
Surge withstand	6 kV conforming to IEC 61000-4-5
Contacts type and composition	1 C/O
[Ith] conventional free air thermal current	3 A for control circuit
Protection type	BS fuse 3 A - for control circuit GB2 circuit breaker 3 A - for control circuit GG fuse 3 A - for control circuit
Maximum power	28 W at 110 V DC conforming to IEC 60947 28 W at 220 V DC conforming to IEC 60947 55 W at 24 V DC conforming to IEC 60947 55 W at 48 V DC conforming to IEC 60947 140 VA at 48 V AC conforming to IEC 60947 360 VA at 110 V AC conforming to IEC 60947 360 VA at 220 V AC conforming to IEC 60947 70 VA at 24 V AC conforming to IEC 60947
[Ui] rated insulation voltage	600 V power circuit conforming to CSA 600 V power circuit conforming to UL 690 V power circuit conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV
Phase failure sensitivity	< 3 s
Reset	Automatic reset 120 s fixed Electrical by interruption of power supply for minimum 0.1 s Manual reset
Time range	0.2...10 s - O-time knob 0.3...10 s - O-time knob 0.5...30 s - D-time knob
Signalling function	2 LEDs
Connections - terminals	Control circuit : cable 1 cable 1...25 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit : cable 1 cable 1...25 mm <sup>2</sup> - cable stiffness: flexible - without cable end Power circuit : cable 1 cable 1...4 mm <sup>2</sup> - cable stiffness: flexible - with cable end Power circuit : cable 1 cable 1.5...10 mm <sup>2</sup> - cable stiffness: flexible - without cable end

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Power circuit : lug-clamp 1 cable 1...4 mm<sup>2</sup> - cable stiffness: flexible - with cable end  
 Power circuit : lug-clamp 1 cable 1.5...10 mm<sup>2</sup> - cable stiffness: flexible - without cable end  
 Control circuit : cable 2 cable 1...25 mm<sup>2</sup> - cable stiffness: flexible - with cable end  
 Control circuit : cable 2 cable 1...25 mm<sup>2</sup> - cable stiffness: flexible - without cable end  
 Control circuit : lug-clamp 1 cable 1...25 mm<sup>2</sup> - cable stiffness: flexible - with cable end  
 Control circuit : lug-clamp 1 cable 1...25 mm<sup>2</sup> - cable stiffness: flexible - without cable end  
 Control circuit : lug-clamp 2 cable 1...25 mm<sup>2</sup> - cable stiffness: flexible - with cable end  
 Control circuit : lug-clamp 2 cable 1...25 mm<sup>2</sup> - cable stiffness: flexible - without cable end

Tightening torque	Control circuit : 0.6...1.2 N.m - on lug-clamp Power circuit : 2 N.m - on cable
Height	67.5 mm
Width	45 mm
Depth	67.5 mm
Product weight	0.172 kg

## Environment

standards	IEC 60255-6 IEC 60947
product certifications	CSA GOST UL
protective treatment	TH conforming to IEC 60068
IP degree of protection	IP20 conforming to IEC 60529
ambient air temperature for operation	-25...60 °C conforming to IEC 60947-4-1
ambient air temperature for storage	-30...80 °C
operating altitude	2000 m
fire resistance	850 °C conforming to IEC 60695-2-1
shock resistance	15 gn 11 ms conforming to IEC 60068-2-7
vibration resistance	4 gn conforming to IEC 60068-2-6
dielectric strength	2 V at 50 Hz conforming to IEC 60255-5
resistance to electrostatic discharge	6 kV in indirect mode 8 kV in air
resistance to radiated fields	10 V/m level 3
resistance to fast transients	2 kV
disturbance radiated/conducted	10 V conforming to EN 61000-4-6 Class A conforming to EN 55011