

LU2B32FU

power base - TeSys U - 32 A - 110...220 V DC
screw clamps control



Main

| | |
|---|---|
| Range | TeSys |
| Product name | TeSys U |
| Device short name | LU2B |
| Product or component type | Reversing power base |
| Device application | Motor |
| Poles description | 3P |
| Suitability for isolation | Yes |
| [Ith] conventional free air thermal current | 32 A |
| Utilisation category | AC-41 AC-43 AC-44 |
| [Uc] control circuit voltage | 110...220 V DC 110...240 V AC 50/60 Hz |

Complementary

| | |
|--|--|
| Auxiliary contact composition | 1 NO + 1 NC |
| Auxiliary contacts type | Type linked contacts (1 NO + 1 NC) conforming to IEC 60947-4-1 Type mirror contact (1 NC) state of the power conforming to draft IEC 60947-1 |
| [Ue] rated operational voltage | 230 V 440 V 500 V 690 V |
| Network frequency | 40...60 Hz |
| [Ie] rated operational current | 21 A at 690 V 23 A at 500 V 32 A at <= 440 V |
| [Ics] rated service breaking capacity | 10 kA 500 V 4 kA 690 V 50 kA 230 V 50 kA 440 V |
| Control circuit voltage limits | 55 V 110...220 V DC drop-out 55 V 110...240 V AC drop-out 88...242 V 110...220 V DC in operation 88...264 V 110...240 V AC in operation |
| Typical current consumption | 1000 mA at 110...220 V DC I maximum while closing 1000 mA at 110...240 V AC I maximum while closing |
| Inrush restraint duration | 15 ms for DC network 25 ms for AC network 50/60 Hz |
| Safety reliability level | B10d 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Operating time | 150 ms with change of direction for power circuit 35 ms opening for control circuit 50 ms closing for control circuit 75 ms without change of direction for power circuit |
| Mechanical durability | 15000000 cycles |
| Operating rate | 60 cyc/mn |
| [Ui] rated insulation voltage | 600 V conforming to UL 508 690 V conforming to IEC 60947-1 3 600 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-6-2 |
| Safe separation of circuit | 400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-------------------------|--|
| Connections - terminals | Power circuit : screw clamp terminals 2 cable 1.5...6 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 1 cable 0.34...1.5 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 1 cable 0.75...1.5 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 1 cable 0.75...1.5 mm ² - cable stiffness: rigid - without cable end Control circuit : screw clamp terminals 2 cable 0.34...1.5 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 2 cable 0.75...1.5 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 2 cable 0.75...1.5 mm ² - cable stiffness: rigid - without cable end Power circuit : screw clamp terminals 1 cable 1...10 mm ² - cable stiffness: rigid - without cable end Power circuit : screw clamp terminals 1 cable 1...6 mm ² - cable stiffness: flexible - with cable end Power circuit : screw clamp terminals 1 cable 2.5...10 mm ² - cable stiffness: flexible - without cable end Power circuit : screw clamp terminals 2 cable 1...6 mm ² - cable stiffness: flexible - with cable end Power circuit : screw clamp terminals 2 cable 1...6 mm ² - cable stiffness: rigid - without cable end |
| Tightening torque | Control circuit : 0.8...1.2 N.m - with screwdriver 5 mm flat Control circuit : 0.8...1.2 N.m - with screwdriver 5 mm Philips no 1 Power circuit : 1.9...2.5 N.m - with screwdriver 6 mm flat Power circuit : 1.9...2.5 N.m - with screwdriver 6 mm Philips No 2 |
| Width | 45 mm |
| Height | 224 mm |
| Depth | 126 mm |
| Product weight | 1.27 kg |

Environment

| | |
|---------------------------------------|--|
| heat dissipation | 3 W for control circuit with LUCA, LUCB, LUCC, LUCD 1.8 W for control circuit with LUCM |
| immunity to microbreaks | 3 ms |
| immunity to voltage dips | 70 % 500 ms conforming to IEC 61000-4-11 |
| product certifications | ABS ASEFA ATEX BV CCC CSA DNV GL GOST LROS (Lloyds register of shipping) UL |
| standards | EN 60947-6-2 IEC 60947-6-2 UL 508 type E with phase barrier CSA C22.2 No 14 type E |
| IP degree of protection | IP20 front panel and wired terminals conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP40 front panel outside connection zone conforming to IEC 60947-1 |
| protective treatment | TH conforming to IEC 60068 |
| ambient air temperature for operation | -25...60 °C with LUCM -25...70 °C with LUCA, LUCB, LUCC, LUCD |
| ambient air temperature for storage | -40...85 °C |
| fire resistance | 650 °C conforming to IEC 60695-2-12 960 °C parts supporting live components conforming to IEC 60695-2-12 |
| operating altitude | 2000 m |
| shock resistance | 10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27 |
| vibration resistance | 2 gn 5...300 Hz power poles open conforming to IEC 60068-2-27 4 gn 5...300 Hz power poles closed conforming to IEC 60068-2-27 |

| | |
|---------------------------------------|--|
| resistance to electrostatic discharge | 8 kV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2 |
| resistance to radiated fields | 10 V/m 3 conforming to IEC 61000-4-3 |
| resistance to fast transients | 2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4 |
| non-dissipating shock wave | 1 kV serial mode conforming to IEC 60947-6-2 2 kV common mode conforming to IEC 60947-6-2 |
| immunity to radioelectric fields | 10 V conforming to IEC 61000-4-6 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0846 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |