

# LUCL18ES

magnetic control unit LUCL 4.5...18 A - 48...72 V - DC



## Main

|                                     |                                                                                                   |
|-------------------------------------|---------------------------------------------------------------------------------------------------|
| Range                               | TeSys                                                                                             |
| Product name                        | TeSys U                                                                                           |
| Device short name                   | LUCL                                                                                              |
| Product or component type           | Magnetic control unit                                                                             |
| Product specific application        | Protection of variable speed drive or soft start/stop unit                                        |
| Product compatibility               | LUFC00<br>LUFN..                                                                                  |
| Utilisation category                | AC-41<br>AC-43<br>AC-44                                                                           |
| Motor power kW                      | 15 kW at 690 V AC 50/60 Hz<br>9 kW at 500 V AC 50/60 Hz<br>7.5 kW at < 400...415 V AC 50/60 Hz    |
| Thermal protection adjustment range | 4.5...18 A                                                                                        |
| [Uc] control circuit voltage        | 48 V AC<br>48...72 V DC                                                                           |
| User language                       | English - setting factory setting<br>English, French, German, Italian, Spanish - setting settable |

## Complementary

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function available             | Manual reset<br>Short-circuit protection                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mounting mode                  | Plug-in                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Mounting location              | Front side                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Control circuit voltage limits | 29 V for AC circuit 48...72 V drop-out<br>29 V for DC circuit 48...72 V drop-out<br>38.5...72 V for AC circuit 48...72 V in operation<br>38.5...93 V for DC circuit 48...72 V in operation                                                                                                                                                                                                                                                           |
| Typical current consumption    | 280 mA at 48...72 V AC I maximum while closing with LUB12<br>280 mA at 48...72 V AC I maximum while closing with LUB32<br>280 mA at 48...72 V DC I maximum while closing with LUB12<br>280 mA at 48...72 V DC I maximum while closing with LUB32<br>35 mA at 48...72 V AC I rms sealed with LUB12<br>35 mA at 48...72 V DC I rms sealed with LUB12<br>45 mA at 48...72 V AC I rms sealed with LUB32<br>45 mA at 48...72 V DC I rms sealed with LUB32 |
| Operating time                 | 35 ms opening with LUB12 for control circuit<br>35 ms opening with LUB32 for control circuit<br>50 ms closing with LUB12 for control circuit<br>50 ms closing with LUB32 for control circuit<br>60 ms closing with LUB12 for control circuit<br>60 ms closing with LUB32 for control circuit<br>70 ms closing with LUB12 for control circuit<br>70 ms closing with LUB32 for control circuit                                                         |
| Load type                      | 3-phase motor - cooling: self-cooled - setting factory setting<br>Single-phase motor                                                                                                                                                                                                                                                                                                                                                                 |
| Tripping threshold             | 14.2 x Ir +/- 20 %                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Reset                          | Automatic reset - setting: setting range<br>Manual - setting: factory setting<br>Manual - setting: setting range<br>Remote reset - setting: setting range                                                                                                                                                                                                                                                                                            |
| Time before reset              | 120 s - reset manual - setting factory setting<br>1...1000 s - reset manual or automatic reset - setting settable                                                                                                                                                                                                                                                                                                                                    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                        |                                                                                                                                                                                                                                                                                                    |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Information displayed                  | Average current - setting factory setting<br>Average current - setting settable<br>Cause of last 5 faults - setting settable<br>Current in phase - setting settable<br>Earth leakage current - setting settable<br>Phase imbalance - setting settable<br>Thermal state of motor - setting settable |
| [Ui] rated insulation voltage          | 600 V conforming to UL 508<br>690 V conforming to IEC 60947-1<br>600 V conforming to CSA C22.2 No 14                                                                                                                                                                                               |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-6-2                                                                                                                                                                                                                                                                   |
| Safe separation of circuit             | 400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1<br>400 V SELV between the control or auxiliary circuit and the main circuit conforming to IEC 60947-1                                                                                                              |
| Product weight                         | 0.135 kg                                                                                                                                                                                                                                                                                           |

## Environment

|                                       |                                                                                                                                                                                    |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| heat dissipation                      | 2 W for control circuit with LUB12<br>3 W for control circuit with LUB32                                                                                                           |
| immunity to microbreaks               | 3 ms                                                                                                                                                                               |
| immunity to voltage dips              | 70 % 500 ms conforming to IEC 61000-4-11                                                                                                                                           |
| standards                             | EN 60947-6-2<br>IEC 60947-6-2<br>UL 508 type E with phase barrier<br>CSA C22.2 No 14 type E                                                                                        |
| product certifications                | CE                                                                                                                                                                                 |
| IP degree of protection               | IP20 front panel and wired terminals conforming to IEC 60947-1<br>IP20 other faces conforming to IEC 60947-1<br>IP40 front panel outside connection zone conforming to IEC 60947-1 |
| protective treatment                  | TH conforming to IEC 60068                                                                                                                                                         |
| ambient air temperature for operation | -25...70 °C                                                                                                                                                                        |
| ambient air temperature for storage   | -40...85 °C                                                                                                                                                                        |
| operating altitude                    | 2000 m                                                                                                                                                                             |
| fire resistance                       | 650 °C conforming to IEC 60695-2-12<br>960 °C parts supporting live components conforming to IEC 60695-2-12                                                                        |
| shock resistance                      | 10 gn power poles open conforming to IEC 60068-2-27<br>15 gn power poles closed conforming to IEC 60068-2-27                                                                       |
| vibration resistance                  | 2 gn 5...300 Hz power poles open conforming to IEC 60068-2-6<br>4 gn 5...300 Hz power poles closed conforming to IEC 60068-2-6                                                     |
| resistance to electrostatic discharge | 8 kV level 3 in open air conforming to IEC 61000-4-2<br>8 kV level 4 on contact conforming to IEC 61000-4-2                                                                        |
| non-dissipating shock wave            | 1 kV serial mode conforming to IEC 60947-6-2<br>2 kV common mode conforming to IEC 60947-6-2                                                                                       |
| resistance to radiated fields         | 10 V/m 3 conforming to IEC 61000-4-3                                                                                                                                               |
| resistance to fast transients         | 2 kV class 3 serial link conforming to IEC 61000-4-4<br>4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4                                               |
| immunity to radioelectric fields      | 10 V conforming to IEC 61000-4-6                                                                                                                                                   |

## Offer Sustainability

|                                  |                                                                       |
|----------------------------------|-----------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1015 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available                                                             |
| Product end of life instructions | Available                                                             |